

PureFlo® Z Series PES Prefiltration Capsules

PureFlo® Z Series PES Prefiltration Capsules are economical, easy-to-use filtration units, designed for effective bioburden and particulate removal in a broad range of applications. The hydrophilic, asymmetric polyethersulfone (PES) membrane demonstrates exceptional throughput capacity and flow performance in aqueous and viscous solutions. The filter capsules are available in a complete spectrum of sizes to simplify scale-up throughout each stage of the development process.

Membrane Configurations

PureFlo® Z Series PES Prefiltration Capsules incorporate a 0.45 or 0.65 μm membrane as well as an optional built-in ZenFlo® highly asymmetric prefilter tailored to enhance filter performance and efficiency in a variety of biopharmaceutical processes.

Connectivity

Saint-Gobain offers the broadest portfolio of standard and custom filter inlet and outlet fittings, simplifying system design by reducing the number of unnecessary connections thereby decreasing the associated risk and cost of adapters. Please refer to the Ordering Information section for a complete list of standard fittings that are available.

Engineered Filtration Solutions

To meet the needs of an innovative and rapidly growing industry, and in addition to the standard product offering, Saint-Gobain offers a collaborative service with a dedicated team of engineers and subject matter experts to develop specialized filtration solutions that are tailored to achieve optimal performance. [Please contact us for more information.](#)

Features / Benefits



Hydrophilic



Gamma-Irradiatable



Optimal Flow



Autoclavable



Asymmetric



Broad Chemical Compatibility



Scalable



Animal-Derived Component Free

Typical Applications

- Buffer
- Cell Culture Media
- Serum
- Ophthalmics
- Reagents
- Biologics

Technical Summary

Materials

Membrane	Polyethersulfone (PES)
Support Material	Polyester (PET)
Molded Components (cage, core, shell, end caps)	Polypropylene (PP) and Nylon*
O-rings (when present)	Silicone

*Except disc filters. Disc filters have polypropylene molded components only.

Membrane Configurations

Membrane	Description	Minimum Bubble Point (at 22 °C, in water)
S045	0.45 µm	2.4 bar 35 psi
S065	0.65 µm	1.6 bar 23 psi
ZS045	0.45 µm PES membrane with built-in 0.65 µm ZenFlo PES prefilter	2.4 bar 35 psi

Measurements (nominal)

Size	Outside Diameter (mm)	Body Length Without Fittings (mm)	Filtration Area (cm ²)	
			Single Layer (S)	ZenFlo (ZS)
Disc (D)	16 - 97	3.7 - 10	0.8 - 60	0.8 - 60
Junior (JZP)	41	41	260	170
Mini (MZP)	59	60	390 - 530	360 - 500
Mid (SZV)	71.5	52 - 257	730 - 5100	650 - 4500
Full (LZ)	90	279 - 1007	6400 - 27000	5700 - 23000

Vent Connections (when present)

	Disc (D)	Junior (JZP)	Mini (MZP)	Mid (SZV)	Full (LZ)
Category	Luer lock w/ cap	Luer lock w/ cap	Luer lock w/ cap	Bleed Valve	Bleed Valve
Connection Type	Female Luer Lock	Female Luer Lock	Female Luer Lock	1/8" hose barb	1/4" hose barb

Operating Conditions (for untreated/non-sterile product)

	Disc (D)	Junior (JZP)	Mini (MZP)	Mid (SZV)	Full (LZ)
Maximum Temperature	80 °C	80 °C	80 °C	80 °C	80 °C
Maximum Inlet Pressure (at 22 °C)	3.1 bar 45 psi	5.5 bar 78 psi	5.5 bar 78 psi	5.5 bar 78 psi	5.5 bar 78 psi
Maximum Forward Differential Pressure (at 22 °C)	3.1 bar 45 psi	5 bar 72.5 psi	5 bar 72.5 psi	5 bar 72.5 psi	5 bar 72.5 psi

Sterilization

Gamma	Up to 50 kGy
Autoclave	Up to 10 cycles at 125 °C for 30 minutes
Ethylene Oxide	Testing is recommended.

Shelf Life

Non-sterile products have a shelf life of 3 years after the date of manufacture.

Traceability

For traceability and easy identification:

- A Certificate of Conformance is provided with each capsule.
- Each filter bag and box are labeled with the product part number, lot number, and identifying characteristics.
- Each Junior, Mini, Mid, and Full size capsule is engraved and labeled with the product part number, lot number, and identifying characteristics.
- Each 25 mm, 40 mm, 65 mm, and 90 mm disc capsule is engraved with the product lot number

Regulatory & Stewardship

Saint-Gobains' PureFlo® Z Series Capsules were designed, manufactured, and qualified with an ISO 13485 certified Quality Management System. For more information, please refer to the product Validation Guide and Regulatory Information Overview (RIO).

Category	Standard or Reference Test
Physiochemical	USP Oxidizable Substances USP <645> Conductivity USP <643> Non-Volatile Residue Total Organic Carbon (TOC) Analysis
Cleanliness	USP <85> Bacterial Endotoxin Test USP <788> Particulate Matter 21 CFR sections 211.72 and 210.3 (b) (6)
Biocompatibility	ASTM F756-17 Hemolysis USP <88> Class VI, and/or USP <87>, and/or ISO 10993-5
Food Contact	21 CFR 177 FDA Indirect Food Additive
Animal-derived Components	No animal-derived material is intentionally added or used during the manufacture of PureFlo® Z Series PES Capsules.
RoHS	Restriction of Hazardous Substances (RoHS 3) Directive 2015/863
REACH	REACH (Registration, Evaluation, Authorisation and Restriction of Chemicals) Article 57, Regulation No. 1907/2006)

Lot Release Criteria

Each PureFlo® Z Series PES capsule product lot is sampled and tested for conformity to the following criteria:

Criteria	Description
Integrity (membrane)	Each filter (100%) in a lot is integrity tested during the manufacturing process.
Integrity (housing)	A representative sample of the lot is tested to meet published burst pressure values.
USP Bacterial Endotoxins	A representative sample from the lot is tested to confirm that an aqueous extraction of the product contains <0.25 EU/mL as determined by the Limulus Amebocyte Lysate (LAL) Test.

PureFlo® Z Series PES Disc Prefiltration Capsules

Saint-Gobain
Life Sciences –
Bioprocess Solutions


PRODUCT TECH SNAPSHOT: (Values are nominal. Please see Technical Summary for additional information)



Filter Size	Body Diameter (mm)	Body Length Without Fittings (mm)	Filtration Area (cm ²)
D13Z	16	3.7	0.8
D25Z	33	5.45	4.6
D40Z	45.5	8	10.5
D50Z	54	8	15.9
D65Z	72	10	26
D90Z	99	10	60

Ordering Guide

PART NUMBER:



PLEASE NOTE:

Not all fittings are available for all filter sizes. Please refer to the next page of the brochure for a standard list of fitting available for each filter size.



Customer Service

50 W. Watkins Mill Rd.
Gaithersburg, MD 20878
Tel: (301) 407-2720
Fax: (240) 566-5774
Email: info.ft@saint-gobain.com

PureFlo® Z Series Disc Capsule Ordering Guide (continued)

Table A. Inlet and outlet fitting option availability

Inlet/Outlet Fitting	Description	D13Z	D25Z	D40Z	D50Z	D65Z	D90Z
OH	1/16" hose barb	•	^	^			
AH	3/32" hose barb	•	^				
1H	1/8" hose barb	•	^	^	•	•	
2H	1/4" hose barb		^	^	^	^	^
2H-FC	1/4" hose barb with filling bell (outlet only)					•	
3H	3/8" hose barb		^	^		^	^
3H-FC	3/8" hose barb with filling bell (outlet only)						•
4H	1/2" hose barb					•	•
5H	5/8" hose barb						•
LF	Female luer lock	•	•	•	•	•	•
LM	Male luer lock	•	•	•	•	•	•
LS	Male luer slip	•	•	•	•		
MT	1/2" tri-clamp					•	•
TC	1 1/2" tri-clamp						•

Table B. Vent fitting availability (located near inlet of capsules when present)

D13Z	D25Z	D40Z	D50Z	D65Z	D90Z
				•	•

• = fitting is available (if it is a hose barb, it is straight)

^ = fitting is available (if it is a hose barb, it is stepped or tapered)



Customer Service

50 W. Watkins Mill Rd.
Gaithersburg, MD 20878
Tel: (301) 407-2720
Fax: (240) 566-5774

Email: info.ft@saint-gobain.com

www.biopharm.saint-gobain.com

Don't see what you're looking for?
Please let us know! We're here to help.

FLS-5366B-10212024-BPS

©2024 Saint-Gobain Life Sciences

PureFlo® Z Series PES Junior Prefiltration Capsules

Saint-Gobain
Life Sciences –
Bioprocess Solutions




PRODUCT TECH SNAPSHOT: (Values are nominal. Please see Technical Summary for additional information)

Body Diameter (mm)	Body Length Without Fittings (mm)	Filtration Area (cm ²)	
		Single Layer (S)	ZenFlo (ZS)
41	41	260	170

Ordering Guide

PART NUMBER:



Customer Service

50 W. Watkins Mill Rd.
Gaithersburg, MD 20878
Tel: (301) 407-2720
Fax: (240) 566-5774

Email: info.ft@saint-gobain.com

www.biopharm.saint-gobain.com

Don't see what you're looking for?
Please let us know! We're here to help.

FLS-5366B-10212024-BPS

©2024 Saint-Gobain Life Sciences

PureFlo® Z Series PES Mini Prefiltration Capsules

Saint-Gobain
Life Sciences –
Bioprocess Solutions




PRODUCT TECH SNAPSHOT: (Values are nominal. Please see Technical Summary for additional information)

Size	Body Diameter (mm)	Body Length Without Fittings (mm)	Filtration Area (cm ²)	
			Single Layer (S)	ZenFlo (ZS)
B	59	60	390	360
C	59	60	440	420
D	59	60	530	500

Ordering Guide

PART NUMBER:



Customer Service

50 W. Watkins Mill Rd.
Gaithersburg, MD 20878
Tel: (301) 407-2720
Fax: (240) 566-5774

Email: info.ft@saint-gobain.com

www.biopharm.saint-gobain.com

Don't see what you're looking for?
Please let us know! We're here to help.

PureFlo® Z Series PES Mid Size Prefiltration Capsules

Saint-Gobain
Life Sciences –
Bioprocess Solutions




PRODUCT TECH SNAPSHOT: (Values are nominal. Please see Technical Summary for additional information)

Size	Body Diameter (mm)	Body Length Without Fittings (mm)	Filtration Area (cm ²)	
			Single Layer (S)	ZenFlo (ZS)
H	71.5	56	730	650
S	71.5	84	1400	1200
L	71.5	141	2600	2300
E	71.5	206	4000	3500
K	71.5	260	5100	4500

Ordering Guide

PART NUMBER:



Customer Service

50 W. Watkins Mill Rd.
Gaithersburg, MD 20878
Tel: (301) 407-2720
Fax: (240) 566-5774

Email: info.ft@saint-gobain.com

www.biopharm.saint-gobain.com

Don't see what you're looking for?
Please let us know! We're here to help.

PureFlo® Z Series PES ZenCap® Full Size Prefiltration Capsules

Saint-Gobain
Life Sciences –
Bioprocess Solutions




PRODUCT TECH SNAPSHOT: (Values are nominal. Please see Technical Summary for additional information)

Size	Body Diameter (mm)	I-line Body Length Without Fittings (mm)	Filtration Area (m ²)	
			Single Layer (S)	ZenFlo (ZS)
1	90	279	0.64	0.57
2	90	522	1.4	1.2
3	90	765	2.0	1.7
4	90	1007	2.7	2.3

Ordering Guide

PART NUMBER:



(1) For I-line capsules, this is the valve closest to the inlet.
For T-line capsules, this is the valve at the 'top' of the capsule.
(2) For T-line capsules, this is the valve closest to the outlet.
For I-line capsules this is the valve at the 'bottom' of the capsule)



Customer Service

50 W. Watkins Mill Rd.
Gaithersburg, MD 20878
Tel: (301) 407-2720
Fax: (240) 566-5774

Email: info.ft@saint-gobain.com

www.biopharm.saint-gobain.com

Don't see what you're looking for?
Please let us know! We're here to help.

PureFlo® Z Series PES Prifiltration Capsule

Saint-Gobain
Life Sciences –
Bioprocess Solutions



PureFlo®, ZenCap®, and ZenFlo® are registered trademarks of Saint-Gobain Life Sciences

Uncontrolled Document - for the controlled version of this document please visit www.biopharm.saint-gobain.com

**Contact us today for:
Consultations • Samples • Quotes • Orders**

**For registered access to Saint-Gobain Product Validation Summaries,
[CLICK HERE](#)**



Customer Service

50 West Watkins Mill Rd.
Gaithersburg, MD 20878

Tel: (301) 407-2720

Fax: (240) 566-5774

Email: info.ft@saint-gobain.com

www.biopharm.saint-gobain.com

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain Performance Plastics products for all intended uses and that the materials to be used comply with all applicable medical regulatory requirements. Saint-Gobain Performance Plastics assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: For a period of 12 months from the date of first sale, Saint-Gobain Life Sciences warrants this product to be free of defects in materials and workmanship. Our only obligation will be to replace any portion proving defective, or at our option, to refund the purchase price thereof.

SAINT-GOBAIN LIFE SCIENCES DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.